



Compacting EPP

Compacting expanded polypropylene at a ratio of up to 50 : 1. The results may vary depending on the quality of the EPP.

SK370

- Save costs for transport and landfill
- Generate income from sale of the compacted blocks
- Save space and handling by dealing with the EPP in a quick and efficient manner
- Save investment and use the same machine to compact EPS



Production Data	Europe	USA
Capacity per hour	App. 200 kg	App. 440 lbs
Density achieved	App. 300 kg/m ³	App. 18 lbs/ft ³
Block measurement	App. 38 cm x 38 cm	App. 14.5" x 14.5"
Energy consumption	Europe	USA
Main motor	15 kW	24 HP (18 kW)
Hydraulic pump	0,55 kW	0.88 HP (0.66 kW)
Pre-crusher HEAVY DUTY	5,5 kW	8.8 HP (6.6 kW)
Cooling system for pressure chamber	0,55 kW	0,88 HP (0.66 kW)
Electrical requirements	Europe	USA
3 phase 400V; 50 Hz (HEAVY DUTY)	63 AMPS	
3 phase 480V; 60 Hz (HEAVY DUTY)		63 AMPS
3 phase 230V; 60 Hz (HEAVY DUTY)		125 AMPS
Dimensions : 09-50091	Europe	USA
Length	5,32 m	17 ft 5 inch
Width	1,33 m	4 ft 4 inch
Height	2,15 m	7 ft 7 inch
Weight	App. 1500 kg	App. 3300 lbs
09-50121 SK370H with HEAVY DUTY pre-crusher for feed by conveyor	09-50122 SK370 with HEAVY DUTY pre- crusher 1400mm wide for widescreen TV packadina frames	09-50091 SK370 45 degree HEAVY DUTY pre- crusher for manual feed

