



Compacting XPS

Compacting extruded polystyrene at a ratio of app. 10 : 1. The results may vary depending on the quality of the XPS.

SK370

- Save costs for transport and landfill
- Generate income from sales of the compacted XPS
- Save space and handling by dealing with the XPS in a quick and efficient manner



Production Data	Europe	USA
Capacity per hour	App. 200-250 kg	App. 440-550 lbs
Density achieved	App. 330 kg/m ³	App. 20 lbs/ft ³
Block measurement	App. 38 cm x 38 cm	App. 14.5" x 14.5"
Energy consumption	Europe	USA
Main motor	15 kW	24 HP (18 kW)
Hydraulic pump	0,55 kW	0.88 HP (0.66 kW)
Pre-crusher HEAVY DUTY	5,5 kW	8.8 HP (6.6 kW)
Electrical requirements	Europe	USA
3 phase 400V; 50 Hz	63 AMPS	
3 phase 480V; 60 Hz		63 AMPS
3 phase 230V; 60 Hz		125 AMPS
Dimensions: 09-50091	Europe	USA
Length	5,38 m	17 ft. 5 inch
Width	1,33 m	4 ft. 4 inch
Height	2,13 m	6 ft. 9 inch
Weight	App. 1000 kg	App. 2200 lbs

09-50106
SK370 – 1000mm wide hopper for
conveyor belt



09-50091
SK370 – 1000mm wide hopper for manual feed.

